

AXIS Camera Station S9101 Desktop Terminal

Optimal surveillance for server installations

AXIS Camera Station S9101 Desktop Terminal is a micro form factor desktop terminal optimized for high-definition surveillance video where space is limited. The terminal is preloaded with AXIS Camera Station software to minimize installation time and complements AXIS S1032 or AXIS S1048 rack servers to create a high performing surveillance workstation. AXIS S9101 has validated hardware and software components for optimal surveillance experience, and includes three-year hardware warranty with on-site replacement service. AXIS S9101 supports two monitors in a dual screen setup for system overview. A universal keyboard and computer mouse are included.

- > **Ease of installation**
- > **AXIS Camera Station software included**
- > **Validated hardware**
- > **On-site replacement service**



AXIS Camera Station S9101 Desktop Terminal

Processor	Intel® Core™ i3-7100T, 3,4 GHz, 3MB Cache, 2C/4T	Mounting option	VESA 100 x 100 mm (3 15/16 x 3 15/16 in)
Memory	8GB (1x8GB) SO-DIMM 2400 MHz DDR4, non ECC	Operating conditions	5 °C to 35 °C (41 °F to 95 °F) Humidity 20–80% (non-condensing)
Storage	M.2 128 GB SATA Solid State Drive	Storage conditions	–40 °C to 65 °C (–40 °F to 149 °F)
Graphic card	Intel® HD Graphics 630	Approvals	FCC Part 15 Subpart B Class B, ICES-003 Class B, VCCI Class B, RCM AS/NZS CISPR 32 Class B, KCC KN32 Class B, KN35, EN 62311, EN 55032, EN 55024, EN/IEC 61000-3-2, EN/IEC 61000-3-3, EAC, BSMI, EN 50564, EN 62623, IEC/EN/UL 60950-1
Operating system	Microsoft Windows 10 IoT 2016 LTSB	Dimensions	182 x 33 x 178 mm (7.2 x 1.4 x 7.0 in)
Video streaming	Live view: Up to 25 camera split views or 1 x 4K camera view Playback: 4 x 1080p camera split views or 1 x 4K camera view Supports two monitors	Weight	1.17 kg (2.58 lb)
General		Included accessories	Installation guide, keyboard (international/US), power supply with cable, computer mouse, mousepad
Power	65 W, external power adapter AC Input 90–264 V, 50/60 Hz	Optional accessories	AXIS T8310 Video Surveillance Control Board
Connectors	6x External USB 3.1 Gen 1 (2 front/4 rear) 1x RJ45 Ethernet 1x HDMI 1.4 1x Display Port 1.2 1x UAJ (Universal Audio Jack) 1x Audio line out	Warranty	Axis 3-year warranty, see www.axis.com/warranty

AXIS Camera Station

For details about AXIS Camera Station features and functions please see Data Sheet on www.axis.com

Environmental responsibility:
www.axis.com/environmental-responsibility