

AXIS T8504-E Outdoor PoE Switch

Managed, plug-and-play outdoor switch

AXIS T8504-E Outdoor PoE Switch is an easy-to-install, compact outdoor switch enabling connection of four PoE-powered devices. The SFP port enables fiber connectivity for long distance connections, and remote management ensures easy maintenance, reducing support cost and customer down time. AXIS T8504-E is a robust system component with a wide temperature range, surge protection, and a dust and water-resistant enclosure which remains assembled during installation. With up to 60 W per port and a total power budget of 150 W, the switch is compatible with all Axis network devices.

- > 60 W per port, total 150 W
- > SFP port
- > Plug-and-play installation
- > Rugged enclosure
- > VAPIX[®] support



AXIS T8504-E Outdoor PoE Switch

Network		Surge protection	6kV on all network ports and AC lines
Security	Password protection HTTPS encryption VLAN	Operating conditions	-40 °C to 50 °C (-40 °F to 122 °F) Humidity 0–90% RH (non-condensing)
Supported protocols	IPv4, IPv6, HTTP, HTTPS, Bonjour, SNMP v1/v2c/v3, DNS, TCP, UDP, IGMP, ICMP, ARP, SSH, RADIUS, TACACS, TELNET, Syslog, 802.1Q (VLAN)	Storage conditions	-40 °C to 85 °C (-40 °F to 185 °F) Humidity 0–90% RH (non-condensing)
Throughput	14.9 Mpps	Approvals	EMC EN 55032 Class B EN 55024 FCC part 15 Subpart B Class B ICES-003 Class B RCM AS/NZS CISPR 32 Class B EN 61000-4-5 Class 5 EN 50121-4 IEC 62236-4 EAC
Switching capacity	20 Gbps	Safety	IEC/EN/UL 60950-1 IEC/EN/UL 60950-22
MAC table	8 K	Environment	IEC 60529 IP67 NEMA 250 Type 4X
Jumbo frames	9216 Bytes	Surge protection	GR-1089-CORE Issue 4 ITU-T K.20
General		Management software	Axis Camera Management
Casing	Aluminum Color: White	Included accessories	Installation Guide Power connector
Environment	Outdoor	Optional accessories	AXIS T91M47 Pole Mount AXIS T8611 SFP Module LC.LX AXIS T8612 SFP Module LC.SX AXIS T8613 SFP Module 1000BASE-T
Dimensions	240 × 166 × 72 mm 8.42 × 5.90 × 2.75 in	Warranty	Axis 3-year warranty and AXIS Extended Warranty option, see www.axis.com/warranty
Weight	2.9 kg (6.39 lbs)	Environmental responsibility: www.axis.com/environmental-responsibility	
Power requirements	100–240 V AC, 50/60 Hz		
PoE class	Power over Ethernet Plus (PoE+) IEEE 802.3at Type 2 Class 4		
PoE output	Port 1 and 2: Up to 60 W Port 3 and 4: Up to 30 W Power budget: 150 W		
Pin assignment	Power over pairs: Port 1 and 2: 1/2, 3/6, 4/5, and 7/8 Port 3 and 4: 1/2 and 3/6		
Connectors	PoE ports RJ45 10Base-T/100Base-TX/1000Base-T Mbps (4x) Uplink SFP port (1x) Power Power connector port		