

AXIS P3915-R Network Camera

High-performance camera with audio for onboard surveillance

AXIS P3915-R is specially designed for HDTV 1080p video surveillance in vehicles. The compact, rugged and discreet indoor camera has IP67-rated protection against dust and water, and can withstand tough conditions such as vibrations, shocks and temperature fluctuations. The active tampering alarm detects tampering attempts, such as blocking or spray-painting. AXIS P3915-R is specially adapted to respond quickly to changes in light levels, ensuring that high image quality is maintained. Traffic Light mode helps distinguishing colors of traffic lights in very dark scenes. The pixel counter helps verifying that the pixel resolution of an object meets specific customer requirements. AXIS P3915-R has audio-in and I/O capabilities.

- > **Compact, rugged design**
- > **HDTV video quality**
- > **Traffic Light mode**
- > **Audio-in**
- > **I/O ports**



AXIS P3915-R Network Camera

Models	AXIS P3915-R: RJ45 AXIS P3915-R: M12	Pre- and post-alarm video or image buffering for recording or upload Notification: email, HTTP, HTTPS, TCP and SNMP trap PTZ: PTZ preset, start/stop guard tour Overlay text, external output activation
Camera		
Image sensor	1/2.8" Progressive scan RGB CMOS	
Lens	3.6 mm, F2.0 Horizontal field of view: 87° Vertical field of view: 47° M12 mount, fixed iris See Optional accessories for exchangeable lenses	
Minimum illumination	Color: 0.2 lux	
Shutter time	1/28000 s to 2 s with 50 Hz 1/33500 s to 2 s with 60 Hz 1/32500 s to 2 s	
Camera angle adjustment	Pan: ±30° Tilt: 15-90° Rotation: ±175°	
Video		
Video compression	H.264 (MPEG-4 Part 10/AVC) Baseline, Main and High Profiles Motion JPEG	
Resolution	1920x1080 to 160x90	
Wide dynamic range	WDR - forensic capture	
Frame rate	Up to 25/30 fps (50/60 Hz) in all resolutions	
Video streaming	Multiple, individually configurable streams in H.264 and Motion JPEG Controllable frame rate and bandwidth VBR/MBR H.264	
Image settings	Compression, color, brightness, sharpness, contrast, white balance, exposure control, exposure zones, WDR - dynamic contrast, backlight compensation, fine tuning of behavior at low light, rotation: 0°, 90°, 180°, 270° including Corridor Format, text and image overlay, privacy mask, mirroring of images, Traffic Light mode	
Pan/Tilt/Zoom	Digital PTZ, preset positions Guard tour, control queue	
Audio		
Audio streaming	Audio in, simplex	
Audio compression	AAC-LC 8/16 kHz, G.711 PCM 8 kHz, G.726 ADPCM 8 kHz Configurable bit rate	
Audio input	External microphone input or line input	
Network		
Security	Password protection, IP address filtering, HTTPS ^a encryption, network access control, digest authentication, user access log, centralized certificate management	
Supported protocols	IPv4/v6, HTTP, HTTPS ^a , SSL/TLS ^a , QoS Layer 3 DiffServ, FTP, SFTP, CIFS/SMB, SMTP, Bonjour, UPnP TM , SNMP v1/v2c/v3 (MIB-II), DNS, DynDNS, NTP, RTSP, RTP, TCP, UDP, IGMP, RTCP, ICMP, DHCP, ARP, SOCKS, SSH	
System integration		
Application Programming Interface	Open API for software integration, including VAPIX [®] and AXIS Camera Application Platform; specifications at www.axis.com AXIS Video Hosting System (AVHS) with One-Click Connection ONVIF [®] Profile S and ONVIF [®] Profile G, specification at www.onvif.org	
Analytics	Included AXIS Video Motion Detection, active tampering alarm ^b , audio detection Supported AXIS Perimeter Defender Support for AXIS Camera Application Platform enabling installation of third-party applications, see www.axis.com/acap	
Event triggers	Analytics, time scheduled, edge storage events Audio level, external input	
Event actions	Record video and audio: SD card and network share Upload images or video clips: FTP, SFTP, HTTP, HTTPS, network share and email	
Data streaming	Event data	
Built-in installation aids	Pixel counter	
General		
Casing	Aluminum and polycarbonate casing	
Sustainability	PVC free	
Mounting	Inside vehicles and rolling stock ^c	
Memory	256 MB RAM, 128 MB Flash	
Power	Power over Ethernet (PoE) IEEE 802.3af/802.3at Type 1 Class 2, max. 4.3 W	
Connectors	RJ45: male, 10BASE-T/100BASE-TX M12: female, rugged, D-coded with rotatable coupling nut All connectors support PoE 3.5 mm audio in connector, mono, I/O 4-pin, 1 input, 1 output + 12 V DC/15 mA	
Storage	Support for microSD/microSDHC/microSDXC card Support for SD card encryption Support for recording to network-attached storage (NAS) For SD card and NAS recommendations see www.axis.com	
Operating conditions	-30 °C to 60 °C (-22 °F to 140 °F) Humidity: 10-95% RH (non-condensing)	
Storage conditions	-40 °C to 65 °C (-40 °F to 149 °F)	
Approvals	EMC EN 55022 Class B, EN 55024, EN 61000-6-1, EN 61000-6-2, EN 61000-3-2, EN 61000-3-3, FCC Part 15 Subpart B Class B, ICES-003 Class B, VCCI Class B, RCM AS/NZS CISPR 22 Class B, KCC KN22 Class B, KN24, EN 50121-4, EN 50121-3-2, IEC 62236-4, ECE R10 rev.04 (E approval), EN 50498 Safety IEC/EN/UL 60950-1, EN 45545 Environment IEC 60529 IP67, NEMA 250 Type 4X, IEC/EN 62262 IK08, EN 50155 Class T3, IEC 60721-3-5 Class 5M3 (vibration and shock), IEC 60068-2-27, IEC 60068-2-64, EN 50581	
Dimensions	Height: 49 mm (1 15/16 in), ø 109 mm (4 3/16 in)	
Weight	RJ45: 285 g (0.63 lb) M12: 293 g (0.65 lb)	
Included accessories	Installation guide, Windows decoder 1-user license, drill hole template, top cover tool, lens tool, Allen key Resistorx [®]	
Optional accessories	Lenses 2.1 mm, F2.2: horizontal field of view 148° 2.8 mm, F2.0: horizontal field of view 105° 6 mm, F1.6: horizontal field of view 52° 8 mm, F1.6: horizontal field of view 40° Other AXIS T96B05 Outdoor Housing, AXIS T94D01S Mount Bracket, AXIS T94D02S Mount Bracket, Network coupler IP66, Network cable coupler indoor For more accessories, see www.axis.com	
Video management software	AXIS Companion, AXIS Camera Station, video management software from Axis' Application Development Partners available on www.axis.com/support/downloads	
Languages	English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Traditional Chinese	
Warranty	Axis 3-year warranty and AXIS Extended Warranty option, see www.axis.com/warranty	

- a. This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (www.openssl.org), and cryptographic software written by Eric Young (ey@cryptsoft.com).
b. For detection of tampering attempts in static and non-crowded scenes.
c. For outdoor applications, use AXIS T96B05 Outdoor Housing.

Environmental responsibility:

