

XWP10 Pressurized Washer Tank

Explosion-protected washer tank

XWP10 Pressurized Washer Tank is made of SAE 316L stainless steel and specially designed for use with explosion-protected cameras. It can be manually pressurized to 4 bar for a maximum head height of 20 meters (65.6 ft). It features an ATEX/IECEX/EAC-approved solenoid release valve, which can be controlled and powered via the network camera. It is ideal for use with cameras located in onshore, offshore, marine and heavy industrial environments. The operating temperature range is -20 °C to 60 °C (-4 °F to 140 °F). XWP10 Pressurized Washer Tank can also be mounted on walls.

- > **Electropolished stainless steel finish (SAE 316L)**
- > **ATEX/IECEX/EAC-certified**
- > **Manually pressurized**
- > **Wall mount possibility**



XWP10 Pressurized Washer Tank

General		
Supported products	Explosion-protected network cameras Explosion-protected PTZ network cameras	IEC/EN 60079-0, IEC/EN 60079-7, IEC/EN 60079-18, IEC/EN 60079-31
Casing	SAE 316L stainless steel	Certifications
Dimensions	413 x 711 x 255 mm (16.3 x 28.0 x 10.0 in) Cable entry (side and bottom): Ø40 mm	ATEX (XWP10A-24) II 2 G Ex e mb IIC T4 Gb II 2 D Ex tb IIIC T135°C Db Certificate: KEMA 98ATEX2542 (solenoid) IECEX (XWP10A-24) Ex e mb IIC T4 Gb Ex tb IIIC T135°C Db Certificate: KEM 08.0002X (solenoid) EAC (XWP10R-24) II Gb T4 X III Db 135°C X Certificate: RU C-GB.0Б01.B.00196
Weight	25 kg (55 lb) (with full tank)	Included accessories
Mounting	Free standing or wall mount	Installation Guide
Power	24 V AC, max 10 W	Warranty
Tank capacity	10 l (2.6 gal)	Axis 3-year warranty, see axis.com/warranty
Tube length	10 m (33 ft)	
Elevation	Up to 20 m (66 ft) at 4 bar (58 psi)	Environmental responsibility: www.axis.com/environmental-responsibility
Operating conditions	-20 °C to 60 °C (-4 °F to 140 °F)	
Approvals	Environment IEC/EN 60529 IP67 Explosion	